

GTO[®]/ACCESS SYSTEMS

PROFESSIONAL RESIDENTIAL

GPX-SL25
SLIDE GATE OPERATOR

For slide gates up to 24 ft. (7.3 m) long, 650 lbs. (294.8 kg) with a 20 ft. (6.1 m) opening.

Technology • Innovation • Quality
Since 1987



Available From:

www.gtoaccess.com



Technology • Innovation • Quality

Since 1987



Pad mount ready package includes battery backup, radio receiver, entry transmitter, AC transformer, and chain. Optional post mount and adjustable pad mount adapters are available.



GPX-SL25

RESIDENTIAL SERIES

For slide gates up to 24 ft. (7.3 m) long, 650 lbs. (294.8 kg) with a 20 ft. (6.1 m) opening.

The GPX-SL25 series will handle gates weighing up to 650 lbs. (294.8 kg) and 24 ft. (7.3 m) in length with a 20 ft. (6.1 m) opening, if all proper installation procedures have been followed.

Note: ball bearing rollers should be used on all gates.

FEATURES:

- ▶ Full systems capable “add on ready” heavy-duty control board includes adjustable obstruction sensing, gate sequencing and auto close settings (OFF and 3–120 seconds).
- ▶ Includes a built-in internal friction disc brake/lock.
- ▶ Optional post mount adapter available (not included).
- ▶ Chain disconnect for manual operation.
- ▶ Residential cycle rated to 100 cycles daily.

MECHANICAL:

- Operating temp -5 F (-21C) to +160 F (71 C).
- Opening time: 1 ft. (.31 m) per second maximum.
- #41 Chain 25 ft. with master link.
- Fully compatible accessory terminal block provides connections for safety loops, exit wands, intercoms, card readers, phone systems.
- Operation, diagnostic and safety alarms,
- Inherent obstruction sensing.

ELECTRICAL/POWER:

- 12 Volt DC / 7.0 amp hour, sealed, rechargeable battery (included). Battery charge is maintained by regulator on control board
- Powered by a reliable 12 Volt (1/4 HP) DC motor, case hardened steel gear reducer.
- “Sleep draw” is 40 mA; “active draw” is 2 to 9 amps.

DIMENSIONS:

Height: 12.5”
Depth: 12”
Width: 10.5”

SHIPPING WEIGHT:

50 lbs. (22.7 kg) Meets UPS shipping standards

WARRANTY:

2 Year (RESIDENTIAL application)

CLASS OF OPERATION:

Class I

SAFETY LISTINGS:

System Certified with UL325 5th Edition safety standards, ETL listed.

OPTIONS:

Solar Power: Second battery recommended (not included). 10-watt Solar Panel Charger (FM123)

Post Mount: requires the optional Post Mount adapter (R4983).

Adjustable Pad Mount Adapter: used to raise operator 6” to 10” above existing pad (R4984)

Dual Gates: For dual gate applications, add Dual Gate Kit (GPX-SL252).

SUGGESTED ACCESSORIES:

- Wireless Vehicle Sensor (R4500)
- Solar Panels (FM123)
- Transmitters (RB741/RB742)
- Digital Keypad (F310)

www.gtoaccess.com



GTO®, GTO/PRO®, Bulldog®, GTO Access Systems®, are trademarks of Gates That Open, LLC (“GTO”), and are the exclusive property of GTO. All rights are reserved by GTO, and these marks may not be used in any form without the prior written permission of GTO. © 2010

rev-10/29/12