

# Residential Single/Dual Swing Gate Operators with Dual Sense Technology

- Cost Efficient Operation
- Quick Installation
- Easy Transmitter Programming
- Soft Start / Soft Stop
- Solar Compatible
- Includes Battery Backup
- Works with All Types of Gates
- 2-Year Warranty
- UL 325 Compliant



**4000XLS**



**3000XLS**



**2000XLS**

# Residential Single/Dual Swing Gate Operators

## 4000XLS | 3000XLS | 2000XLS

### Common Electrical Features

- 12 Volt DC / 7.0 amp hour, sealed, rechargeable battery (included). Battery charge is maintained by a 120V AC/60 Hz input, 18V AC, 40 VA. output, transformer, regulated to 14V DC through control board
- Powered by a reliable 12 Volt (120 Watt) DC motor, 16:1 planetary gear drive system
- “Sleep draw” is 15 mA;  
“active draw” is 3 to 7 amps


### Common Engineering Features

- The control board can be programmed for pull-to-open or push-to-open
- Operating temp -5 F (-21C) to +160 F (71 C)
- Opening time: From 15 to 20 seconds
- Range of arm stroke: is up to 15”(33 cm) with 2000XLS, is up to 16”(41 cm) with 3000XLS, and is up to 21”(53 cm) with 4000XLS,
- Operator length for 2000XLS: with arm fully retracted is 33.75” (85.2 cm), mounting point to mounting point
- Operator length for 3000XLS: with arm fully retracted is 40.25” (102 cm)
  - The PRO-SW3200XLS works as a second gate operator when combined with a PRO-SW3000XLS. The PRO-SW3200XLS includes a 40ft power cable.
- Operator length for 4000XLS: with arm fully retracted is 46.25” (117 cm)
  - The PRO-SW4200XLS works as a second gate operator when combined with a PRO-SW4000XLS. The PRO-SW4200XLS includes a 50ft power cable
- Operation, diagnostic and safety alarms
- Inherent obstruction sensing
- Soft start/soft stop—for long mechanical life expectancy
- Auto close adjustable 3–120 seconds delay

All Models Listed;  
UL325 Compliant



MODEL	TYPE	VOLTS	Max. Gate Length	Max Gate Weight	Gate Speed
PRO-SW4000XLS	Single	12 V DC	20'	1000 lbs	18-20 sec
PRO-SW4200XLS	Dual				



MODEL	TYPE	VOLTS	Max. Gate Length	Max Gate Weight	Gate Speed
PRO-SW3000XLS	Single	12 V DC	16'	650 lbs.	15-18 sec.
PRO-SW3200XLS	Second Arm				



MODEL	TYPE	VOLTS	Max. Gate Length	Max Gate Weight	Gate Speed
PRO-SW2000XLS	Single	12 V DC	16'	500 lbs.	15-20 sec
PRO-SW2002XLS	Dual				

### CAUTIONS



- Automatic gates not for pedestrians
- Automatic gate operators designed for vehicular traffic only; operators are powerful and can cause serious injury or death; DIRECT ALL PEDESTRIAN TRAFFIC TO SEPARATE PEDESTRIAN GATE

LINEAR™

www.linear-solutions.com



Supporters and Proud Members of